

CLAIMS:

1. A diesel engine with a supercharger including a
supercharger for taking in and pressurizing outside air and
5 supplying the pressurized supercharged air into a cylinder, and
a heat exchanger, which is provided in a supercharged air
passage from an outlet port of said supercharger to an inlet port
of said cylinder and cools the supercharged air from said
supercharger,
- 10 wherein said heat exchanger is a hybrid type of heat
exchanger comprising
a first heat exchanger for carrying out heat exchange between
the supercharged air from the outlet port of said supercharger
and a first heat exchange medium, and
15 a second heat exchanger for carrying out heat exchange between
the supercharged air from an outlet port of said first heat
exchanger and a second heat exchange medium having higher
temperature than said first heat exchange medium, and
supplying the supercharged air after the heat exchange with
20 said second heat exchange medium to said cylinder.
2. The diesel engine with the supercharger in accordance
with Claim 1,
wherein the engine is a water cooling type of engine
25 with the supercharger using cooling water,

wherein said first heat exchange medium is outside air,
and

wherein said second heat exchange medium is cooling
water from said water cooling type of engine.

5

3. The diesel engine with the supercharger in accordance
with Claim 1,

wherein a fuel used is a water emulsion fuel.

10 4. The diesel engine with the supercharger in accordance
with Claim 3,

wherein the engine is a water cooling type of engine
with the supercharger using cooling water,

wherein said first heat exchange medium is outside air,

15 and

wherein said second heat exchange medium is cooling
water from said water cooling type of engine.

5. The diesel engine with the supercharger in accordance
20 with Claim 1 or Claim 3, further comprising:

load detecting means for detecting load of the engine;

and

control means for receiving a detection signal from said
load detecting means and controlling flow of said second heat
25 exchange medium.

6. The diesel engine with the supercharger in accordance with Claim 2 or Claim 4, further comprising:

load detecting means for detecting load of said water cooling type of engine; and

5 control means for receiving a detection signal from said load detecting means and controlling flow of cooling water from said water cooling type of engine.

7. The diesel engine with the supercharger in accordance with Claim 1 or Claim 3, further comprising:

a pressure sensor which is provided between an outlet port of a compressor of said supercharger and an inlet port of said cylinder and detects supercharged air pressure; and

15 control means for receiving a detection signal from said pressure sensor and controlling flow of said second heat exchange medium,

wherein the engine is used at an almost constant engine speed.

20 8. The diesel engine with the supercharger in accordance with Claim 2 or Claim 4, further comprising:

a pressure sensor which is provided between an outlet port of a compressor of said supercharger and an inlet port of said cylinder and detects supercharged air pressure; and

25 control means for receiving a detection signal from said

pressure sensor and controlling flow of cooling water from said water cooling type of engine,

wherein said water cooling type of engine is used at an almost constant engine speed.

5

9. A diesel engine with a supercharger including a supercharger for taking in and pressurizing outside air and supplying the pressurized supercharged air into a cylinder, and a heat exchanger, which is provided in a supercharged air passage from an outlet port of said supercharger to an inlet port of said cylinder and cools the supercharged air from said supercharger,

10

wherein a fuel used is a fuel inferior to light oil in ignitability, and

15

wherein said diesel engine with the supercharger comprises means for maintaining temperature of the supercharged air supplied to said cylinder at a predetermined value.

FOR FILED IN 03450300